

SIRIUS B0967A

(EN ISO 20345-2022) S1PL ESD FO SR

(EN ISO 20345-2011) S1P ESD SRC

SMART EVO Line



SmellStop

3D hi-tech fabric lining for the best breathability with permanent antibacterial treatment*, it prevents the proliferation of bacteria and bad odors

Sizes: 36 – 48

Width



Adjustable self adhesive fasteners

Seamless upper

Dry'n Air^{ESD}

Anatomic removable DRY'N AIR ESD footbed, with the air circulation system.



Fresh'n Flex

Ballistic fabric midsole
Perforation 0 mm
Standard 20345:2011
(Nail 4,5mm – Force 1100 Newton).

AirTech SINGLE DENSITY

Flexible and light anti fatigue Sole

It is appropriate to any surface type. High resistance to slipping by liquids

SlimCap

- Metal free toe-cap: lighter
- Cap's thickness reduced, 35% less weight compared to the market standard weight.
- Equipped with a perfect, preshaped protective stripe to avoid the painful pressure on toes,



*SmellStop: Treatment made with biocide Zinc pyrithione (CAS-No. 13463-41-7) product type PT 09 who counteracts the deposit of microorganisms on the surface of materials.

THE CONTENTS OF THIS SHEET ARE COPYRIGHT OF BASE PROTECTION. THE REPRODUCTION, EVEN PARTIAL, IS FORBIDDEN